




LMR BATTERY SPECIFICATIONS	PART NUMBER
	PM9858LIPIC

COMPATIBLE RADIOS	Motorola XTS1500, XTS2500, MT1500, PR1500
REPLACES OEM BATTERY	NNTN7335, NNTN7554, PMNN4495
COMPATIBLE CHARGERS	Endura EC1-MT13B, EC1M-MT13B, EC2M-MT13-D, EC6M-MT13B, EC12M-MT13-D, EVC-MT13, EVC-MT13-4 / Motorola adaptive IMPRES 1 and 2 chargers
VOLTAGE	7.4V
CAPACITY	4100 mAh / 30.3 Wh
CHEMISTRY	LiPo
CELL TYPE	PolyMax HPC™
OPERATING TEMPERATURE	-10° C to +50° C (discharge) / 0° C to +45° C (charge)
CHARGE CYCLES	>500
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Yes (Motorola conditioning chargers)
PROTECTION TYPES	Over-charge / over-discharge / over-temperature
HOUSING MATERIAL	ABS
HOUSING SEAL	Ultrasonic weld
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	Included
WARRANTY	24 months (capacity 80%) 24 months (materials and workmanship)
PRODUCT PHOTO	 <p>PolyMax HPC™ Lithium Polymer • Maximum Energy</p>