

Criticalbattery.com

LMR BATTERY SPECIFICATIONS	PART NUMBER
	CKNBL3LI-48

COMPATIBLE RADIOS	Kenwood NX-5000, NX-5200, NX-5300, NX-5400, TK-5230, TK-5330, TK-5430, VP5000, VP5230, VP5330, VP5430, VP6000, VP6230, VP6330, VP6430, VP8000
REPLACES OEM BATTERY	KNB-L3M
COMPATIBLE CHARGERS	Endura EC1-KW4A, EC1M-KW4A, EC6M-KW4A, EC2M-KW4A-D, EC12M-KW4A-D / EVC-KW4, EVC-KW4-4 / Kenwood KSC-32
VOLTAGE / CAPACITY	7.4V / 4800 mAh / 35.5 Wh
CHEMISTRY	Li-Ion
CELL TYPE	Samsung INR21700-50E or equivalent
OPERATING TEMPERATURE	-20° C to +60° C (discharge) / 0° C to +45° C (charge)
CHARGE CYCLES	500
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Yes (conditioning not required for cycle life or battery run time)
PROTECTION TYPES	Short circuit / over-charge / over-discharge / over-temperature monitoring via charge contact
HOUSING MATERIAL / SEAL	ABS / ultrasonic weld
INGRESS PROTECTION	IP68 rated
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	N/A
WARRANTY	12 months
PRODUCT PHOTO	 Dimensions (H x W x D): 4.59" x 2.28" x 1.22" 116.7 x 57.7 x 31.1 mm Weight: 0.44 lbs. / 200.0 g.